

DRWG No
10-2925

THIRD ANGLE PROJECTION. DIMNS. IN MM

INTERLOCKING FEATURE

SPLIT LINE

GROOVES FOR ST. STEEL STRAPS

1500

MOULDED HINGE

'A'

HINGED OPEN POSITION

FOR $\phi 42$ CABLE, A= $\phi 100$. WEIGHT IN AIR 11.6kg, WEIGHT IN WATER 1.7kg.

DATE 14Feb'00				<p>CWA DESIGN COPYRIGHT NOT TO BE USED OR RE- PRODUCED WITHOUT EXPRESS PERMISSION FROM CWA</p> <p>CWA PRODUCTS LIMITED HOOK BASINGSTOKE HANTS</p>	<p>TOLERANCES :- UNLESS OTHERWISE STATED NO DEC PLACE ± 0.5 ANGULAR $\pm 1/4^\circ$ 1 DEC PLACE ± 0.3 2 DEC PLACE ± 0.15 HOLES UP TO 12.7mm $+0.10mm -0$ ALL COAXIAL DIAS CONCENTRIC WITHIN 0.05mm ALL HOLES ON PITCH CIRCLES WITHIN 0.10mm OF TRUE POS.</p>	<p>REMOVE ALL SHARP EDGES WITH 0.40 RAD OR CHAMFER UNLESS OTHERWISE STATED</p>	MATERIAL	FINISH	<p>SURFACE FINISH 0.8 UNLESS OTHERWISE STATED</p>
DRAWN fjj							CWA100 POLYURETHANE	DRWG No.	
SCALE NTS	14Feb'00		1				10-2925	TITLE	
CHECKED	DATE	C.NOTE	ISS				$\phi 42$ CABLE PROTECTION PROPOSAL		