


DRWG No  
10-3162

THIRD ANGLE PROJECTION. DIMNS. IN MM

STEEL INTERFACE BRACKET  
WELDED TO JUNCTION BOX

TRANSITION PIECE 10-3165

INTERFACE CLAMP 10-3164



LOCK-OUT RADIUS  
R4500

CABLE BEND RESTRICTOR SEGMENTS, RIGID POLYURETHANE  
25 INTERLOCKING 'ARMADILLO' SEGMENTS, OVERALL LENGTH 10m, SEE DRG. 10-3155

TRANSITION PIECE 10-3163

10000 OA

SEA BED

FLEXIBLE CABLE PROTECTION, CWA100 POLYURETHANE  
5 SECTIONS OF CWA CABLE PROTECTION, SEE DRG. 10-3154

DO NOT EXCEED 3000kg LOAD AT 180° UNSUPPORTED

DATE 8Nov'02				CWA DESIGN COPYRIGHT NOT TO BE USED OR RE- PRODUCED WITHOUT EXPRESS PERMISSION FROM CWA	TOLERANCES :- UNLESS OTHERWISE STATED NO DEC PLACE ±0.5 ANGULAR ±1/4° 1 DEC PLACE ±0.3 2 DEC PLACE ±0.15 HOLES UP TO 12.7mm +0.10mm -0 ALL COAXIAL DIAS CONCENTRIC WITHIN 0.05mm ALL HOLES ON PITCH CIRCLES WITHIN 0.10mm OF TRUE POS.	REMOVE ALL SHARP EDGES WITH 0.40 RAD OR CHAMFER UNLESS OTHERWISE STATED	MATERIAL	FINISH	SURFACE FINISH 0.8 UNLESS OTHERWISE STATED
DRAWN fjj							DRWG No. 10-3162		
SCALE NTS	8Nov'02		1	<b>CWA PRODUCTS LIMITED HOOK BASINGSTOKE HANTS</b>			TITLE ø250 CABLE PROTECTION SYSTEM PROPOSAL		
CHECKED	DATE	C.NOTE	ISS						