



CABLE PROTECTION PERFORMANCE:-
6000lb AT R600 AT ±22.5'

STRAIGHT LINE AXIAL LOAD, 40,000lb

WEIGHT IN AIR, 100lb
WEIGHT IN WATER 55lb

DATE	20May'97		
DRAWN	fjj		
SCALE	NTS		
CHECKED	20May'97		1
	DATE	C.NOTE	ISS

CWA DESIGN COPYRIGHT
NOT TO BE USED OR RE-
PRODUCED WITHOUT EXPRESS
PERMISSION FROM CWA

TOLERANCES :- UNLESS OTHERWISE STATED
NO DEC PLACE ±0.5 ANGULAR ±1/2°
1 DEC PLACE ±0.3 2 DEC PLACE ±0.15
HOLES UP TO 12.7mm +0.10mm -0
ALL COAXIAL DIAS CONCENTRIC WITHIN 0.05mm
ALL HOLES ON PITCH CIRCLES WITHIN 0.10mm OF TRUE POS.

REMOVE ALL SHARP
EDGES WITH 0.40 RAD
OR CHAMFER UNLESS
OTHERWISE STATED

MATERIAL

FINISH

DRWG No.

50-3034-00

SURFACE
FINISH
D.B.
UNLESS
OTHERWISE
STATED

CWA PRODUCTS LIMITED HOOK BASINGSTOKE HANTS

TITLE

TOW POINT PROTECTOR