



CABLE PROTECTION PERFORMANCE:-
 8000kg, TOTAL, AT R600 AT ±22.5°, (45° TOTAL)
 2000kg, TOTAL, AT R600 AT ±45°, (90° TOTAL)

STRAIGHT LINE AXIAL LOAD, 18200kg
 WEIGHT IN AIR 45.4kg
 WEIGHT IN WATER 25kg
 WEIGHT OF CENTRE TOW SWIVEL SHACKLE 18.2kg
 SWIVEL TOW LOAD 61000kg, MAX PEAK.

| | | | | | | | | | | |
|---------|----------|---|--|--|--|--|----------|--|--|----------|
| DATE | 6Nov'98 | | | CWA DESIGN COPYRIGHT NOT TO BE USED OR RE- PRODUCED WITHOUT EXPRESS PERMISSION FROM CWA | TOLERANCES :- UNLESS OTHERWISE STATED NO DEC PLACE ±0.5 ANGULAR ±1/4° 1 DEC PLACE ±0.3 2 DEC PLACE ±0.15 HOLES UP TO 12.7mm +0.10mm -0 ALL COAXIAL DIAS CONCENTRIC WITHIN 0.05mm ALL HOLES ON PITCH CIRCLES WITHIN 0.10mm OF TRUE POS. | REMOVE ALL SHARP EDGES WITH 0.40 RAD OR CHAMFER UNLESS OTHERWISE STATED | MATERIAL | FINISH | SURFACE FINISH D.B. UNLESS OTHERWISE STATED | |
| DRAWN | fjj | | | | | | | | | DRWG No. |
| SCALE | 18Feb'99 | 2 | | | | | | | | |
| CHECKED | 6Nov'98 | 1 | | | | | TITLE | CENTRE LINE SWIVEL TOW POINT PROTECTOR | | |

CWA PRODUCTS LIMITED HOOK BASINGSTOKE HANTS