



CABLE PROTECTION PERFORMANCE:-
 1500kg AT R600 AT ± 22.5°
 STRAIGHT LINE AXIAL LOAD 40,000lb
 WEIGHT IN AIR 122.8lb
 WEIGHT IN WATER 67.5lb

DATE 15Mar'99				CWA DESIGN COPYRIGHT NOT TO BE USED OR RE- PRODUCED WITHOUT EXPRESS PERMISSION FROM CWA	TOLERANCES :- UNLESS OTHERWISE STATED NO DEC PLACE ±0.5 ANGULAR ±1/4° 1 DEC PLACE ±0.3 2 DEC PLACE ±0.15 HOLES UP TO 12.7mm +0.10mm -0 ALL COAXIAL DIAS CONCENTRIC WITHIN 0.05mm ALL HOLES ON PITCH CIRCLES WITHIN 0.10mm OF TRUE POS.	REMOVE ALL SHARP EDGES WITH 0.40 RAD OR CHAMFER UNLESS OTHERWISE STATED	MATERIAL	FINISH	SURFACE FINISH G.S. UNLESS OTHERWISE STATED
DRAWN fjj			AS PER COMPONENT				NATURAL		
SCALE NTS	15Mar'99	1					DRWG No.	50-3042-04	
CHECKED	DATE	C.NOTE	ISS				TITLE	GUN UMBILICAL BEND STIFFENER	
CWA PRODUCTS LIMITED HOOK BASINGSTOKE HANTS									